

M A T E R I A L S A F E T Y D A T A S H E E T

URATONE FLAT DEEP BASE

Page: 1

HMIS CODES: H F R P
1 0 0 A

PRODUCT CODE: DF01

=====SECTION I - MANUFACTURER IDENTIFICATION=====

MANUFACTURER'S NAME: HARRIS PAINTS COMPANY
ADDRESS : PO BOX 364723
SAN JUAN, P.R. 00936-4723

EMERGENCY PHONE : 800-424-9300 CHEMTRE DATE PRINTED : 04/22/02
INFORMATION PHONE : 787-798-1005 NAME OF PREPARER : DAVID MUNOZ

=====SECTION II - HAZARDOUS INGREDIENTS=====

REPORTABLE COMPONENTS	CAS NUMBER	VAPOR PRESSURE mm HG @ Temp	Weight Percent
ACETIC ACID VINYL ESTER ACGIH/TLV-STEL: 25 PPM OSHA PEL-TWA: 100 PPM	108-05-4		0.03
FORMALDEHYDE ACGIH/TLV:0.3PPM TWA:0.75PPM	50-00-0		0.01
ACETALDEHYDE ACGIH TLV-STEL: 25 PPM OSHA PEL-TWA: 100 PPM	75-07-0		0.01

INDICATES TOXIC CHEMICAL (S) SUBJECT TO THE REPORTING REQUIREMENTS OF SECTION 313 OF TITLE III AND OF 40 CFR 372.

=====SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS=====

BOILING RANGE: NOT DETERMINED
VAPOR DENSITY: NOT DETERMINED
COATING V.O.C. : 0.27 lb/gl
SOLUBILITY IN WATER: WATER SOLUBLE
APPEARANCE AND ODOR: MILD ODOR.

SPECIFIC GRAVITY (H2O = 1): 1.28
EVAPORATION RATE: NOT DETERMINED
MATERIAL V.O.C. : 0.09 lb/gl

=====SECTION IV - FIRE AND EXPLOSION HAZARD DATA=====

FLASH POINT: NON FLAMMABLE
FLAMMABLE LIMITS IN AIR BY VOLUME-LOWER: n/a
METHOD USED: NONE
UPPER: n/a

EXTINGUISHING MEDIA: Respiratory equipment should be worn to avoid inhalation of concentrated vapors. Water should not be used except as fog to keep nearby containers cool.

SPECIAL FIREFIGHTING PROCEDURES
EXTINGUISH MEDIA: FOAM, CO2, DRY CHEMICAL, WATER FOG

UNUSUAL FIRE AND EXPLOSION HAZARDS

Due to pressure build-up, closed containers exposed to extreme heat may explode. During emergency conditions, over-exposure to decomposition products may cause a health hazard. Symptoms may not be immediately apparent. Obtain medical attention.

=====SECTION V - REACTIVITY DATA=====

STABILITY: STABLE

M A T E R I A L S A F E T Y D A T A S H E E T

URATONE FLAT DEEP BASE

Page: 2

CONDITIONS TO AVOID:

Excessive heat, poor ventilation, corrosive atmospheres, excessive aging.

INCOMPATIBILITY (MATERIALS TO AVOID) :

Alkaline materials, strong acids and oxidizing materials.

HAZARDOUS DECOMPOSITION OR BYPRODUCTS:

May cause hazardous fumes when heated to decomposition. Fumes may contain carbon monoxide, carbon dioxide, oxides of nitrogen and oxides of metals listed in section II. Fumes may also contain oxides of nitrogen.

HAZARDOUS POLYMERIZATION: Will not occur.

=====SECTION VI - HEALTH HAZARD DATA=====

INHALATION HEALTH RISKS AND SYMPTOMS OF EXPOSURE

INHALATION: Dizziness, breathing difficulty, headaches & loss of coordination.

SKIN AND EYE CONTACT HEALTH RISKS AND SYMPTOMS OF EXPOSURE

Primary irritation.

SKIN ABSORPTION HEALTH RISKS

IRRITATION.

INGESTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE

Can cause gastrointestinal irritation, vomiting, nausea and diarrhea.

HEALTH HAZARDS (ACUTE AND CHRONIC)

PROLONGED AND REPEATED BREATHING OF SPRAY MIST AND/OR SANDING DUST OVER A PERIOD OF YEARS MAY CAUSE LUNG DISEASE.

CARCINOGENICITY: NTP CARCINOGEN: NO IARC MONOGRAPHS: NO OSHA REGULATED: NO

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE

None when used in accordance with Safe Handling and Use information, (See section VII)

EMERGENCY AND FIRST AID PROCEDURES

Inhalation overexposure - Move person to fresh air. If breathing stops, apply artificial respiration and seek immediate medical attention. Eye contact-flush with large quantities of water for 15 minutes. Skin contact - Wash thoroughly with soap and water. Ingestion - Do not induce vomiting, can cause chemical pneumonitis and pulmonary edema. Contact physician immediately.

SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED

Eliminate ignition sources, provide good ventilation, dike spill area and add absorbent earth or sawdust to spilled liquid. Thoroughly wet with water and mix.

WASTE DISPOSAL METHOD

Collect adsorbent/water/spilled liquid mixture into metal containers and add enough water to cover. Consult local state and federal hazardous regulation before disposing into approved hazardous waste landfills. Obey relevant law.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING

Use non-sparking utensils when handling this material. Avoid hot metal surface. Keep away from excessive heat and open flames. KEEP OUT OF REACH OF CHILDREN.

OTHER PRECAUTIONS

NONE.

=====SECTION VIII - CONTROL MEASURES=====

RESPIRATORY PROTECTION

When spraying this material use a NIOSH approved cartridge respirator or gasmask suitable to keep airborne mists and vapor concentration below thresholdlimit values. When using in poorly ventilated and confined spaces, use a fresh air supplying respirator or a self-contained breathing apparatus.

VENTILATION

General mechanical ventilation or local exhaust should be suitable to keep vapor concentrations below TLV. Ventilation equipment must be explosion proof.

PROTECTIVE GLOVES

NOT REQUIRED.

EYE PROTECTION

Do not get in eyes. Safety eyewear with splash guards or sideshields is recommended to prevent contact.

OTHER PROTECTIVE CLOTHING OR EQUIPMENT

NOT REQUIRED.

WORK/HYGIENIC PRACTICES

Eye washes and safety showers in the workplace is recommended.

=====SECTION IX - DISCLAIMER=====

To the best of our knowledge, the information contained here is accurate, obtained from sources believed to be accurate. We neither guarantee that any hazards mentioned are the only ones which exists. The manner of that use and whether there is any infringement of patents is the sole responsibility of the user.